NSN 2530-00-907-5970

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-907-5970 **Body Material:** Steel First End Outside Diameter: **2.743** inches **Mounting Provision:** Unthreaded mounting holes **Tempurature Rating:** Not rated **Overall Height:** 4.185 inches **Bore Diameter:** 3.000 inches **Body Outside Diameter:** 3.500 inches **Overall Diameter:** 3.500 inches First End Hole Diameter: 1.000 inches First End Thickness At Mounting Holes: 1.500 inches **Compressed Length:** 17.500 inches **Extended Length:** 24.500 inches **Mounting Provision Arrangement Style:** Two hole **Pressure Rating:** Not rated **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Bearing type **Mounting Type And Location:** Tongue cylinder head end **Mounting Facility Diameter:** Any acceptable **Center To Center Distance Between Mounting Provisions:** 15.000 inches

Port Location And Quantity:

1 piston rod end

NSN 2530-00-907-5970

Linear Actuating Cylinder Assembly - Page 2 of 2



| Port Style: |
|----------------------------------|
| Gasket seal |
| Port Thread Series Designator: |
| Unf |
| Port Thread Diameter: |
| 0.437 inches |
| Port Thready Qty Per Inch (tpi): |
| 20 |
| Port Thread Class: |
| 2b |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A34200