NSN 2530-00-937-2541

Pneumatic Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-937-2541

| Ply Rating: |
|-----------------------------------|
| 8 |
| Inside Diameter: |
| 19.805 inches |
| Slot Depth: |
| 0.285 inches |
| Groove Depth: |
| 1.600 inches |
| Overall Height: |
| 1.947 inches |
| Overall Width: |
| 8.837 inches |
| Mounting Hole Diameter: |
| 1.215 inches |
| Mounting Hole Quantity: |
| 6 |
| Ring Style: |
| Rim side ring slotted |
| Effective Width: |
| 7.562 inches |
| Mounting Bolt Circle Diameter: |
| 8.750 inches |
| Pilot Hole Diameter: |
| 6.471 inches |
| Size Designator: |
| 9.00 |
| Design Type: |
| Integral rim |
| Design Form: |
| Disk |
| Hub: |
| Not included |
| Rim: |
| Included |
| Ring: |
| Included |
| Mounting Type For Which Designed: |
| Single tire |
| Disk Type: |
| Single |
| Inside Circumference: |

62.220 inches

NSN 2530-00-937-2541Pneumatic Tire Wheel - Page 2 of 2



| Lightening Hole: |
|---|
| ncluded |
| Valve Hole Shape: |
| Slotted |
| Tire Rim Diameter: |
| 20.000 inches |
| Tire: |
| ncluded |
| Mounting Face Type: |
| Concave |
| Offset Distance From Rim Centerline To Outside Wheel Mounting Face: |
| 5.188 inches |
| Rim Style: |
| 28 |
| Ring Type For Which Designed: |
| Side |
| Bolt/stud Mounting Facility: |
| Not included |
| Hub Characteristic: |
| Demountable |
| Lightening Hole Quantity: |
| 3 |
| Lightening Hole Hub Cap Mounting Feature: |
| Not included |
| Fsc Application Data: |
| Mobility kit, launcher, guided missile |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| Г307-s |
| |