## NSN 2530-00-943-2626

Tread Pattern:

Solid Rubber Tire Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2530-00-943-2626

Smooth tread
Overall Length:
3.250 inches
Mounting Hole Diameter:
Any acceptable
Mounting Hole Quantity:
1
Bearing Surface Width:
3.563 inches
Mounting Bolt Circle Diameter:
Any acceptable
Pilot Hole Diameter:
Any acceptable
Size Designator:
8 by 3 by 6-1/2
Load Capacity:
850.000 pounds
Tire Type:
Solid, flat tread
Design Type:
Solid cast disk
Hub:
Not included
Rim:
Included
Bearings:
Included
Bearing Quantity:
1
Bearing Inside Diameter:
0.750 inches
Bearing Type:
Tapered roller
Tire:
Included
<b>Hub Cap Mounting Feature:</b>
Not included
<b>Hub Characteristic:</b>
Integral
Hub Style:

## NSN 2530-00-943-2626

Solid Rubber Tire Wheel - Page 2 of 2



Rim Characteristic:
Integral
Integral Rim Type:
Flat base
Lubrication Fitting:
Not provided
Tire Characteristic:
Integral
Tire Arrangement Characteristic:
Single
Offset Distance From Rim Centerline To Outside Of Wheel Mounting:
Any acceptable
Axle Recess Diameter:
1.750 inches
Material:
Aluminum
Material:
Aluminum
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T307-t