## NSN 2530-01-030-2476

**Body Material:** 

Steel

Linear Actuating Cylinder Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/2530-01-030-2476



First End Outside Diameter: 2.445 inches **Mounting Provision:** Pin **Tempurature Rating:** Not rated **Mounting Facility Length:** 1.000 inches **Overall Height:** 3.000 inches **Overall Width:** 2.312 inches **Bore Diameter:** Any acceptable **Body Outside Diameter:** 2.250 inches First End Hole Diameter: 1.000 inches First End Thickness At Mounting Holes: 0.870 inches **Compressed Length:** 19.500 inches **Extended Length:** 25.875 inches **Pressure Rating:** Not rated **Integral Valve Operation Method:** Hydraulic **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: Bearing type **Mounting Type And Location:** Tongue cylinder head end **Mounting Facility Diameter:** 1.000 inches **Port Location And Quantity:** 1 piston rod end Port Style: Gasket seal

## NSN 2530-01-030-2476

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Thread Series Designator:
Unf
Port Thread Diameter:
0.562 inches
Port Thready Qty Per Inch (tpi):
18
Port Thread Class:
2b
Special Features:
Self-aligning bearings on piston rod end and mtg end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A34200