

View Online at <https://aerobasegroup.com/nsn/2530-01-101-8357>

General Description:

Fcover, steel, carbon, spec qq-s-698, 0.0897 in. Thk, hole 0.500 in. Dia, 1.375 in. W; drum, iron, casting, spec qq-i-652, 10 holes 0.469 in. Dia, 13.875 id, 18.000 od; bolt, steel, spec ff-b-575, 7/16-20 unf thd, 0.688 in. Thd lg, 1.688 in. O/a lg; slinger, steel, carbon, spec qq-s-698, 10 holes 0.516 in. Dia, 10.000 id, 14.000 od; spacer, iron, malleable, spec qq-i-666, 10 holes 0.976 in. Dia, 8.719 id, 13.750 od; hub, iron ductile, casting, 10 holes 0.976 min 0.980 maximum in. Dia, chamfered 0.062 by 45 deg, 10 holes 0.501 min 0.502 maximum in. Dia, 1/2-13 unc thd; adapter, steel, carbon, spec qq-s-635, 10 holes 0.467 min 0.459 maximum in. Dia, 10 holes 0.512 min 0.518 maximum in. Dia, 6 holes 0.375 in. Dia, 6.618 min 6.622 maximum id; 15.719 min 15.750 maximum od

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No