

View Online at <https://aerobasegroup.com/nsn/2540-00-287-8228>

Mounting Type:

Any acceptable

Heat Medium Type:

Air

Heat Outlet Quantity:

1

Heat Delivery Direction:

Horizontal

Heat Discharge Outlet Type:

Stationary

Heat Directing Device:

Flexible ducts and hinged door

Air Circulation Device:

Squirrel cage blower

Speed Adjustments:

Two speed

Maximum Air Flow Rate:

68.0 cubic feet per minute

Circulated Air Type:

Heated

Radio Interference Suppression Type:

Army, mil-s-10379, radio suppression

Flue Connection Location:

On bottom side 7.047 in.From air discharge end

Width:

18.969 inches

Current Type:

Dc

Depth:

6.500 inches

Prime Mover Type:

Electric motor

Operating Control Type:

Hand switch

Current Rating In Amps:

6.0

Heating Element Type:

Burner and combustion chamber

Ignition Method:

Electrode

Inclosure Material:

Any acceptable

Fuel Consumption Rate Per Hour:

0.4 gallons

Heat Delivery Rate:

30000.0 british thermal unit

Fuel Feed Method:

Internal pump

Voltage In Volts:

24.0

Height:

9.500 inches

Quantity:

1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A01300