

View Online at https://aerobasegroup.com/nsn/2540-00-287-8228

Mounting Type:
Any acceptable
Heat Medium Type:
Air
Heat Outlet Quantity:
1
Heat Delivery Direction:
Horizontal
Heat Discharge Outlet Type:
Stationary
Heat Directing Device:
Flexible ducts and hinged door
Air Circulation Device:
Squirrel cage blower
Speed Adjustments:
Two speed
Maximum Air Flow Rate:
68.0 cubic feet per minute
Circulated Air Type:
Heated
Radio Interference Suppression Type:
Army, mil-s-10379, radio suppression
Flue Connection Location:
On bottom side 7.047 in. From air discharge end
Width:
18.969 inches
Current Type:
Dc
Depth:
6.500 inches
Prime Mover Type:
Electric motor
Operating Control Type:
Hand switch
Current Rating In Amps:
6.0
Heating Element Type:
Burner and combustion chamber
Ignition Method:
Electrode
Inclosure Material:
Any acceptable



Fuel Consumption Rate Per Hour: 0.4 gallons Heat Delivery Rate: 30000.0 british thermal unit Fuel Feed Method: Internal pump Voltage In Volts: 24.0 Height: 9.500 inches Quantity: 1 Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A01300