NSN 2540-00-288-4963

Compartment Vehicular Heater - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2540-00-288-4963 **Mounting Type:** Any acceptable **Heat Medium Type:** Air **Maximum Pressure Limit:** 2.0 pounds per square inch gage **Heat Outlet Quantity:** 1 **Heat Delivery Direction:** Horizontal **Heat Discharge Outlet Type:** Stationary **Heat Directing Device:** Fixed louver Air Circulation Device: Propeller fan **Speed Adjustments:** Six speed **Maximum Air Flow Rate:** 71.0 cubic feet per minute **Circulated Air Type:** Heated **Radio Interference Suppression Type:** Army, mil-s-10379, radio suppression Flue Connection Location: Exhaust tube located on bottom 0f heater Diameter: 6.031 inches **Current Type:** Dc **Prime Mover Type:** Electric motor **Operating Control Type:** Hand switch **Current Rating In Amps:** 6.0 **Heating Element Type:** Burner **Ignition Method:** Electrode

Inclosure Material: Stainless steel

NSN 2540-00-288-4963

Compartment Vehicular Heater - Page 2 of 2



Fuel Consumption Rate Per Hour:
4.0 gallons
Heat Delivery Rate:
32400.0 british thermal unit
Fuel Feed Method:
Internal pump
Voltage In Volts:
24.0
Fuel Type:
80/87 octane gasoline
Height:
10.468 inches
Quantity:
1
Surface Treatment:
Enamel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: