NSN 2540-00-555-9230

Compartment Vehicular Heater - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2540-00-555-9230 **Mounting Type:** Any acceptable **Heat Medium Type:** Air **Heat Outlet Quantity: Heat Delivery Direction:** Vertical **Heat Discharge Outlet Type:** Stationary **Heat Directing Device:** Fixed louver Air Circulation Device: Squirrel cage blower **Speed Adjustments:** Two speed **Maximum Air Flow Rate:** 225.0 cubic feet per minute **Circulated Air Type:** Heated **Radio Interference Suppression Type:** Army, mil-e-53301, radio suppression Flue Connection Location: On top 9.625 in. From base Width: 8.156 inches **Current Type:** Dc Depth: 24.188 inches **Prime Mover Type:** Gasoline engine **Operating Control Type:** Thermostatic **Current Rating In Amps:** 9.0 **Heating Element Type:** Combustion chamber **Ignition Method:** Electrode **Inclosure Material:**

Any acceptable

NSN 2540-00-555-9230

Compartment Vehicular Heater - Page 2 of 2



Fuel Consumption Rate Per Hour:
Not rated
Heat Delivery Rate:
60000.0 british thermal unit
Fuel Feed Method:
Internal pump
Voltage In Volts:
24.0
Fuel Type:
80/87 octane gasoline and 91/96 octane gasoline and 100/130 octane gasoline
Height:
11.750 inches
Quantity:
1
Surface Treatment:
Any acceptable
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A01300