NSN 2540-00-777-4072

Compartment Vehicular Heater - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2540-00-777-4072 **Mounting Type:** Any acceptable **Heat Medium Type:** Hot water **Maximum Pressure Limit:** Any acceptable **Heat Outlet Quantity: Heat Delivery Direction:** Vertical **Heat Discharge Outlet Type:** Stationary **Heat Directing Device:** Adjustable louver **Air Circulation Device:** Squirrel cage blower **Speed Adjustments:** Single speed **Maximum Air Flow Rate:** Any acceptable **Circulated Air Type:** Heated **Radio Interference Suppression Type:** Army, mil-s-10379, radio suppression Width: Between 8.188 inches and 8.312 inches **Current Type:** Dc Depth: 9.000 inches **Prime Mover Type:** Electric motor **Operating Control Type:**

Hand switch **Current Rating In Amps:** 4.0 **Heating Element Type:** Hot water coil **Ignition Method:** Electrode **Inclosure Material:** Any acceptable

NSN 2540-00-777-4072

Compartment Vehicular Heater - Page 2 of 2



| Heat Delivery Rate: |
|--|
| 20000.0 british thermal unit |
| Fuel Feed Method: |
| Any acceptable |
| Voltage In Volts: |
| 24.0 |
| Fuel Type: |
| 91/96 octane gasoline |
| Height: |
| Between 15.312 inches and 15.438 inches |
| Quantity: |
| 1 |
| Surface Treatment: |
| Enamel |
| Specification Data: |
| 81349-mil-h-31993 government specification |
| Specification Or Standard: |
| 2 type and a capacity |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A01300 |