

View Online at <https://aerobasegroup.com/nsn/2540-00-880-8251>

**Mounting Type:**

Any acceptable

**Heat Medium Type:**

Air

**Heat Outlet Quantity:**

1

**Heat Delivery Direction:**

Horizontal

**Heat Discharge Outlet Type:**

Stationary

**Heat Directing Device:**

Adjustable louver

**Air Circulation Device:**

Squirrel cage blower

**Speed Adjustments:**

Single speed

**Maximum Air Flow Rate:**

80.0 cubic feet per minute

**Circulated Air Type:**

Heated

**Radio Interference Suppression Type:**

Army, mil-s-10379, radio suppression

**Flue Connection Location:**

On mtg bracket side 1.813in.From air discharge end

**Width:**

10.188 inches

**Current Type:**

Dc

**Depth:**

5.500 inches

**Prime Mover Type:**

Electric motor

**Operating Control Type:**

Hand switch

**Current Rating In Amps:**

4.1

**Heating Element Type:**

Combustion chamber

**Ignition Method:**

Glow plug

**Inclosure Material:**

Any acceptable

**Fuel Consumption Rate Per Hour:**

0.3 gallons

**Heat Delivery Rate:**

15000.0 british thermal unit

**Fuel Feed Method:**

External pump

**Voltage In Volts:**

12.0

**Fuel Type:**

Jp-4 jet fuel and df-a arctic diesel fuel oil

**Height:**

8.375 inches

**Quantity:**

1

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A01300