## NSN 2540-01-433-3491



Hydraulic Motor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/2540-01-433-3491 **Thread Direction:** Right-hand **Mounting Type:** Face **Bolt Circle Diameter:** 3.940 inches Thread Size: .438-20 **Shaft Diameter:** 0.985 inches **Bolt Hole Quantity: Operating Speed At Rated Capacity In Rpm:** 3500.0 **End Application:** SANG-LA-V(S-)232 **Bolt Hole Diameter:** 0.350 inches **Drive Shaft Type:** Woodruff keyway **Screw Thread Series Designator:** Unf **Shaft Rotation Direction:** Counterclockwise **Distance From End To Keyway Center:** 0.700 inches **Thread Location:** Internal **Connection Quantity: Connection Type: Maximum Working Pressure Rating At Specificationified Tempurature Range:** 4000psi max **Connection Design:** Threaded **Bolt Hole Thread Size:** .438-20 Sae Key Size Accommodated:

1010

**Displacement Type:** 

Constant

## NSN 2540-01-433-3491

Hydraulic Motor - Page 2 of 2



Constant Dispiacement i en itevolution	Constant	Displacement	Per	Revolution
--	----------	--------------	-----	------------

0.098 cubic inches

Connection Government Specification/std:

Ti sae standard

**Bolt Hole Spacing:** 

90deg by deg

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

T103-f