

View Online at <https://aerobasegroup.com/nsn/2540-01-644-5733>

Mounting Hole Quantity:

2

Mounting Hole Type:

Plain and through hole

Mounting Method:

Bolted

End Application:

2355-01-557-4546; truck materials handling

Design Type:

Straight

Wheel:

Not provided

Tread Surface Type:

Nonslip

Protective Pads:

Not included

Side Rail Length:

998.4 millimeters

Crosspiece Type And Quantity:

3 rung

Crosspiece Length:

260.0 millimeters

Crosspiece Tread:

Included

Safety Shoes:

Not included

Attachment Hooks:

Not included

Product Name:

Ladder, lhs truck

Heat Treatment:

H-32 strain hardened, stabilized to 1/4 hard

Material:

Aluminum alloy 6061, type 6 rail support

Material Specification:

Astm b209 assn standard 1st material response and astm b209 assn standard 2nd material response or astm b221 assn standard 2nd material response

Surface Treatment:

Primer-hexavalent chromium free and primer-lead and hexavalent chromium free and carc (chemical agent resistant coating), aliphatic polyurethane or polyurethane paint-lead, cadmium and hexavalent chromium free

Surface Treatment Specification:

Mil dtl 5541 military standard 1st treatment response and military dtl 53084 military standard 2nd treatment response and military dtl 53039 military standard 3rd treatment response or military dtl 64159 military standard 3rd treatment response and def standard 595 federal standard 3rd treatment response

Shelf Life:

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T325-a