NSN 2540-01-644-7847

Small Arms-fragmentation Protective Supplemental Armor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/2540-01-644-7847 |
|---|
| Mounting Type: |
| Bolt down |
| Mounting Hole Diameter: |
| 0.485 inches all holes |
| Mounting Hole Quantity: |
| 15 |
| Mounting Hole Type: |
| Countersunk and through hole all holes |
| Overall Thickness: |
| 0.250 inches |
| End Application: |
| 2350-01-575-0951; carrie, ammunition, tracked |
| Component Quantity: |
| 1 |
| Component Document Origin: |
| Government |
| Document Source: |
| 19207 |
| Document Type: |
| Engineering drawing |
| Usage Design: |
| Full-tracked vehicle and combat vehicle |
| Design Type: |
| Metal |
| Mounting Position: |
| Side panel and rear and right side |
| Mounting Attachment: |
| Not included |
| Hardness Rating: |
| Between 40.0 rockwell c and 48.0 rockwell c |
| Product Name: |
| Plate, armor, t1-lower sidewall, right rear |
| Vehicle Identification Designator: |
| M992a3 |
| Color Chip Number: |
| 33446 |
| Heat Treatment: |
| Tempered |
| Color: |
| Tan, 686a |
| Material |

Steel, armor

NSN 2540-01-644-7847

Small Arms-fragmentation Protective Supplemental Armor - Page 2 of 2



| Material Specification: |
|--|
| Mil dtl 12560 military standard single material response |
| Surface Treatment: |
| Painted |
| Shape: |
| Irregular |
| Surface Treatment Specification: |
| Fed standard 595 federal standard 2nd treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: T312-w