

View Online at https://aerobasegroup.com/nsn/2590-00-185-6882

| Body Material: | |
|--|--|
| Any acceptable | |
| First End Outside Diameter: | |
| 0.750 inches | |
| Tempurature Rating: | |
| Not rated | |
| Overall Height: | |
| 12.625 inches | |
| Bore Diameter: | |
| Any acceptable | |
| Overall Diameter: | |
| 2.625 inches | |
| First End External Thread Length: | |
| 0.750 inches | |
| Compressed Length: | |
| Any acceptable | |
| Extended Length: | |
| Any acceptable | |
| Pressure Rating: | |
| Not rated | |
| Integral Valve Operation Method: | |
| Hydraulic | |
| Design Characteristics: | |
| Single acting single cylinder | |
| First Piston Rod End Style: | |
| External threaded | |
| First Piston Rod End Thread Series Designator: | |
| Unf | |
| First Piston Rod End Thread Diameter: | |
| 0.750 inches | |
| First Piston Rod End Thready Qty Per Inch (tpi): | |
| 16 | |
| First Piston Rod End Thread Class: | |
| 3a | |
| First Piston Rod End Thread Direction: | |
| Right-hand | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

NSN 2590-00-185-6882

Linear Actuating Cylinder Assembly - Page 2 of 2

Fiig: A34200

