NSN 2590-00-238-9117

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2590-00-238-9117 **Body Material:** Any acceptable First End Outside Diameter: 0.500 inches **Mounting Provision:** Unthreaded mounting holes **Overall Height:** 2.500 inches **Overall Width:** 1.875 inches **Bore Diameter:** 1.000 inches First End External Thread Length: 0.875 inches **Compressed Length:** 11.531 inches **Extended Length:** 19.031 inches **Mounting Facility Circle Diameter:** 2.000 inches **Mounting Provision Arrangement Style:** Four hole bolt circle **Pressure Rating:** 2000.0 pounds per square inch **Design Characteristics:** Double acting single cylinder First Piston Rod End Style: External threaded First Piston Rod End Thread Series Designator: Unf First Piston Rod End Thread Diameter: 0.375 inches First Piston Rod End Thready Qty Per Inch (tpi): 24 **First Piston Rod End Thread Class:** 2a **First Piston Rod End Thread Direction:** Right-hand **Mounting Type And Location:**

Flange center section

Mounting Facility Diameter:

0.201 inches

NSN 2590-00-238-9117

Linear Actuating Cylinder Assembly - Page 2 of 2



Port Location And Quantity:
1 piston rod end
Port Style:
Gasket seal
Port Thread Series Designator:
Npt
Port Thread Diameter:
0.250 inches
Port Pipe Thread Size:
0.250 inches
Special Features:
Mtg holes countersunk 0.376 in.Min/0.385 in.Max diameter by100.0 deg
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A24200