NSN 2590-00-247-6635

Body Material: Any acceptable

2.500 inches

Overall Height: 6.250 inches Overall Width: 6.250 inches

Mounting Provision:

First End Outside Diameter:

Unthreaded mounting holes

Linear Actuating Cylinder Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2590-00-247-6635

| Bore Diameter: | |
|---|------|
| 5.000 inches | |
| First End Hole Diameter: | |
| 1.265 inches | |
| First End Thickness At Mounting Holes: | |
| 3.250 inches | |
| Compressed Length: | |
| 28.125 inches | |
| Extended Length: | |
| 43.625 inches | |
| Pressure Rating: | |
| 2500.0 pounds per square inch | |
| Design Characteristics: | |
| Double acting single cylinder | |
| First Piston Rod End Style: | |
| Ring type | |
| Mounting Type And Location: | |
| Ring cylinder head end | |
| Mounting Facility Diameter: | |
| 1.265 inches | |
| Port Location And Quantity: | |
| 1 piston rod end | |
| Port Style: | |
| Gasket seal | |
| Port Thread Series Designator: | |
| Npt | |
| Port Thread Diameter: | |
| 0.750 inches | |
| Port Pipe Thread Size: | |
| 0.750 inches | |
| Special Features: | |
| Mtg facility has 2.500 in.Od and is 6.000 in.Thk at mtg l | hole |
| | |
| | |
| | |

NSN 2590-00-247-6635

Linear Actuating Cylinder Assembly - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A34200