

View Online at <https://aerobasegroup.com/nsn/2590-00-933-6259>

**General Description:**

6finish, chemical film type and grade optl, class 2, spec mil-c-5541, prime per specification tt-p-666, enamel od specification tt-e-529 or tt-e-485, 2 holes 0.260 plus 0.016 in. Dia, 1/4-20 unc 2b, 0.500 in. Deep, hle 3/8-16 unc 2b, 0.680 in. Deep by csk 90 degrees to 0.391 plus 0.016 in. Dia, consists of, blade no. 11605646 aluminum alloy 6061, spec qq-a-250/11, 14.000 in. H; 27.625 in. Lg; 0.500 in. Thk, bearing no. 1088308 tube steel carbon specification qq-t-830, 2.186 in. Dia, 1.927 in. Lg, screw no. Ms35190-289 2 ea, pin no. 10936370 steel, carbn bar, 0.375 in. Dia, 1.750 in. Lg, socket no. 10922128, 1.062 in. W; 1.875 in. H, pate no. 11605647, reinforcement nos. 11605650 2 ea, 11605649, 11605648, support nos. 11605643, 116054644, bearing nos. 10888346, 10888347, plate no. 11605653 2 ea, catch no. 11605654

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli