

View Online at <https://aerobasegroup.com/nsn/2590-01-241-9137>

End Application:

Engine w/container ce6v53d6v

Second Leg Width:

Between 37.940 inches and 38.060 inches

First Leg Slot Length:

Between 0.970 inches and 1.030 inches

First Leg Slot Width:

Between 0.590 inches and 0.650 inches

Second Leg Hole Diameter:

Between 0.497 inches and 0.506 inches

Second Leg Distance Between Hole Centers Along Width:

Between 11.900 inches and 11.960 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 25.340 inches and 25.520 inches

Second Leg Distance From Edge To Hole Center Along Length:

2.620 inches

First Leg Width:

Between 37.940 inches and 38.060 inches

First Leg Distance Between First And Second Hole Centers Along Width:

Between 1.470 inches and 1.530 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

Between 30.940 inches and 31.060 inches

First Leg Distance From Edge To Hole Center Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Length:

1.500 inches

First Leg Distance Between Third And Fourth Hole Centers Along Width:

Between 1.470 inches and 1.530 inches

Second Leg Hole Arrangement Style:

133

Special Features:

Item contains 2 gusset p/n11650213-3 cage 19207 welded per specification mil-std1261, class 2

Material:

Steel

Material Specification:

Astm-a36 military specification single material response

Surface Treatment:

Primer and enamel

Surface Treatment Specification:

Tt-p-664 military specification 1st treatment response and mil-e-52793 military specification 2nd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

spec.