

View Online at <https://aerobasegroup.com/nsn/2590-01-241-9137>

**End Application:**

Engine w/container ce6v53d6v

**Second Leg Width:**

Between 37.940 inches and 38.060 inches

**First Leg Slot Length:**

Between 0.970 inches and 1.030 inches

**First Leg Slot Width:**

Between 0.590 inches and 0.650 inches

**Second Leg Hole Diameter:**

Between 0.497 inches and 0.506 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 11.900 inches and 11.960 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 25.340 inches and 25.520 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

2.620 inches

**First Leg Width:**

Between 37.940 inches and 38.060 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

Between 1.470 inches and 1.530 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

Between 30.940 inches and 31.060 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.500 inches

**First Leg Distance Between Third And Fourth Hole Centers Along Width:**

Between 1.470 inches and 1.530 inches

**Second Leg Hole Arrangement Style:**

133

**Special Features:**

Item contains 2 gusset p/n11650213-3 cage 19207 welded per specification mil-std1261, class 2

**Material:**

Steel

**Material Specification:**

Astm-a36 military specification single material response

**Surface Treatment:**

Primer and enamel

**Surface Treatment Specification:**

Tt-p-664 military specification 1st treatment response and mil-e-52793 military specification 2nd treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

spec.