NSN 2590-01-262-5279

Linear Actuating Cylinder Assembly - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/2590-01-262-5279 |
|---|
| Body Material: |
| Steel |
| First End Outside Diameter: |
| 3.250 inches |
| Second End Outside Diameter: |
| 4.000 inches |
| Bore Diameter: |
| 5.000 inches |
| First End Hole Diameter: |
| Between 2.005 inches and 2.010 inches |
| Second End Hole Diameter: |
| Between 2.001 inches and 2.003 inches |
| First End Thickness At Mounting Holes: |
| Between 3.620 inches and 3.690 inches |
| Second End Thickness At Mounting Holes: |
| Between 6.940 inches and 7.000 inches |
| Compressed Length: |
| 30.880 inches |
| Extended Length: |
| 48.620 inches |
| Pressure Rating: |
| 3000.0 pounds per square inch |
| ntegral Valve Operation Method: |
| Hydraulic |
| Design Characteristics: |
| Single acting single cylinder |
| First Piston Rod End Style: |
| Ring type |
| Piston Rod End Similarity: |
| Not identical |
| Second Piston Rod End Style: |
| Bearing type |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |

A34200