

View Online at <https://aerobasegroup.com/nsn/2590-01-485-8343>

Prime Mover Quantity:

2

Power Drive Operating Pressure:

1300.0 pounds per square inch gage

Environmental Protection:

Dust-ignition proof and oilproof and watertight

End Application:

Truck, utility (2320-01-413-3739)

Inclosure Type:

Partially enclosed

Duty Cycle:

Continuous

Drum Flange To Flange Distance And Location:

9.000 inches first drum

Drum Diameter And Location:

6.380 inches first drum

Drum Flange Diameter And Location:

6.500 inches first drum

Capstan Spool Mounting Position:

Horizontal

Capstan Spool Style:

Straight head

Capstan Spool Surface Design:

Plain

Capstan Spool Quantity:

1

Load Limit At Selected Speed And Drum Location:

4000.0 pounds single speed first drum

Retrieval Winding Method:

Overwind

Gear Housing Location And Quantity:

1 right of drum

Drive End Location:

Any acceptable

Power Requirement Rating:

56.0 watts

Drum Surface Design:

Grooved

Winch Length:

25.000 inches

Largest Diameter And Location:

7.250 inches first spool

Overall Length And Location:

25.000 inches first spool

Cooling Method:

Water-hydrogen cooled

Product Name:

Winch and motor assembly

Special Features:

Item is hydraulic

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02800