

View Online at https://aerobasegroup.com/nsn/2610-00-051-9306

Application Design:
Truck and bus
Size Designation:
7.00-17
Body Material:
Rubber, synthetic
Inflation Device Type:
Tr75a
Inflation Device Position:
On center
Construction:
Regular
Base Construction:
Standard
Splice Minimum Rated Tensile Strength:
Splice Minimum Rated Tensile Strength: 500 pounds per square inch
500 pounds per square inch
500 pounds per square inch Min. Tensile Strength (psi):
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard:
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Shelf Life:
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Shelf Life: N/a
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Shelf Life: N/a Unit Of Measure:
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Shelf Life: N/a Unit Of Measure:
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Shelf Life: N/a Unit Of Measure: Demilitarization:
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Shelf Life: N/a Unit Of Measure: Demilitarization: No