

View Online at https://aerobasegroup.com/nsn/2610-00-051-9354

Application Design:Truck and busSize Designation:8.25-18Body Material:Rubber, syntheticInflation Device Type:Tr177aInflation Device Position:On centerConstruction:RegularBase Construction:StandardSplice Minimum Rated Tensile Strength:500 pounds per square inchMin. Tensile Strength (psi):1200 pounds per square inchSpecification Or Standard:2 groupDeparture From Cited Document:As medified by eize
Size Designation: 8.25-18 Body Material: Rubber, synthetic Inflation Device Type: Tr177a Inflation Device Position: On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
8.25-18 Body Material: Rubber, synthetic Inflation Device Type: Tr177a Inflation Device Position: Tr177a Inflation Device Position: On center Construction: Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: Sto0 pounds per square inch Signo pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Body Material:Rubber, syntheticInflation Device Type:Tr177aInflation Device Position:On centerConstruction:RegularBase Construction:StandardSplice Minimum Rated Tensile Strength:500 pounds per square inchMin. Tensile Strength (psi):1200 pounds per square inchSpecification Or Standard:2 groupDeparture From Cited Document:
Rubber, syntheticInflation Device Type:Tr177aInflation Device Position:On centerConstruction:RegularBase Construction:StandardSplice Minimum Rated Tensile Strength:500 pounds per square inchMin. Tensile Strength (psi):1200 pounds per square inchSpecification Or Standard:2 groupDeparture From Cited Document:
Inflation Device Type: Tr177a Inflation Device Position: On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Tr177a Inflation Device Position: On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Inflation Device Position: On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Splice Minimum Rated Tensile Strength:500 pounds per square inchMin. Tensile Strength (psi):1200 pounds per square inchSpecification Or Standard:2 groupDeparture From Cited Document:
500 pounds per square inch Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Min. Tensile Strength (psi): 1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
1200 pounds per square inch Specification Or Standard: 2 group Departure From Cited Document:
Specification Or Standard: 2 group Departure From Cited Document:
2 group Departure From Cited Document:
Departure From Cited Document:
-
As modified by size
As modified by size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A009a0