

View Online at <https://aerobasegroup.com/nsn/2610-00-204-2545>

**Tread Pattern:**

Cross country

**Maximum Inflation Pressure:**

50.0 pounds per square inch

**End Application:**

12-ton trailers, mdt crane, 5-ton m812 chassis, and m821 bridge transporter

**Features Provided:**

Flaps

**Tire Air Retention Method:**

Tube type

**Tire Ply Arrangement:**

Bias

**Tire Load Maximum Capacity:**

6410.0 pounds load limits

**Tire Strength:**

F load range

**Tire And Size Designation:**

14.00-20 numeric

**Service Type:**

Over the road truck-bus

**Special Features:**

Nondirectional cross country (ndcc) tire. Tire purchase includes flap. Inner tube may be used 2610-00-051-9464; tire specification is restricted to approved manufacture's p/n gov-28 cage 31270 (denman tire co.) additional manufacturers must be pre-approved per sae j 2014.; warning: do not mix bias and radical tires on the same vehicle. Mixing bias tires with radial tires on the ame vehicle can result in loss of vehicle control, injury to personnel and damage to equipment

**Material:**

Rubber natural

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A504s0