NSN 2610-00-204-4091

Vehicular Pneumatic Tire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2610-00-204-4091

Tread Pattern:
Highway regular
Maximum Inflation Pressure:
75.0 pounds per square inch
End Application:
Army: 5kg fuel tanker trailer & 22.5 ton trailer; m131 trailer tanker, fuel, 5kg; m131a2 trailer tanker, fuel, 5kg; m131a3c trailer tanker,
ruel, 5kg; m871 trailer, flatbed, 22 1/2 ton; m871a1 trailer, tac, 22 1/2 ton.
Features Provided:
Flaps
Tire Air Retention Method:
Tube type
Tire Ply Arrangement:
Bias
Tire Load Maximum Capacity:
5205.0 pounds load limits
Tire Strength:
Fload range
Tire And Size Designation:
11.00-20 numeric
Service Type:
Over the road truck-bus
tem Type Category:
Гіге
Special Features:
M871 basic is authorized to use bias ply tire nsn (2610-00-204-4091) or radial ply tire nsn (2610-01-281-0675) warning: never mix bias ply
ires with radial ply tires on the same vehicle/equipment! Approved manufacturers are listed in cat-I-1922 additional manufacturers must be
ore-approved per astm-1922
Material:
Rubber natural
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A504s0