

View Online at https://aerobasegroup.com/nsn/2610-00-444-7575

Application Design:         Industrial tractor         Size Designation:         6.90%.00-9         Body Material:         Rubber, natural and rubber, synthetic         Inflation Device Type:         Tr135         Inflation Device Position:         On center         Construction:         Regular         Base Construction:         Standard         Splice Minimum Rated Tensile Strength:         500 pounds per square inch         Operating Tempurature Range In Deg Celsius:         -53.89 to 51.67         Min. Tensile Strength (psi):         1200 pounds per square inch         Accessory Type:         Inner tube         Special Features:         Dual size army: used on 4k forklift         SpecialFeatures:         Unit Of Measure:		
Size Designation: 6.90/6.00-9 Body Material: Rubber, natural and rubber, synthetic Inflation Device Type: Tr135 Inflation Device Position: On center Construction: Regular Base Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inter tube Special Features: Dual size army: used on 4k forklift Special Features: Special Feature		
6.906.00-9 Body Material: Rubber, natural and rubber, synthetic Inflation Device Type: Tr135 Inflation Device Position: On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: S00 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: Na Unit Of Measure: Tuto Departure Internet Int		
Rubber, natural and rubber, synthetic         Inflation Device Type:         Tr135         Inflation Device Position:         On center         Construction:         Regular         Base Construction:         Standard         Splice Minimum Rated Tensile Strength:         500 pounds per square inch         Operating Tempurature Range In Deg Celsius:         -53.89 to 51.67         Min. Tensile Strength (psi):         1200 pounds per square inch         Accessory Type:         Inner tube         Special Features:         Dual size army: used on 4k forklift         Specification Or Standard:         5 type         Departure From Cited Document:         As modified by size         Sheff Life:         Na         Dual Size army:         Unit Of Measure:         -         Thied Type:         Na         Dual Size in Size i	-	
Inflation Device Type: Tr135 Tr135 Inflation Device Position: On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Sheff Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Body Material:	
Inflation Device Type: Tr135 Tr135 Inflation Device Position: On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Sheff Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Rubber, natural and rubber, synthetic	
Infation Device Position: On center Construction: Regular Base Construction: Standard Splice Minimum Rated Tensile Strength: S00 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig:		
On center         Construction:         Regular         Base Construction:         Standard         Splice Minimum Rated Tensile Strength:         500 pounds per square inch         Operating Tempurature Range In Deg Celsius:         -53.89 to 51.67         Min. Tensile Strength (psi):         1200 pounds per square inch         Accessory Type:         Inner tube         Specification Or Standard:         5 type         Departure From Cited Document:         As modified by size         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No         Fig:	Tr135	
Construction:         Regular         Base Construction:         Standard         Splice Minimum Rated Tensile Strength:         500 pounds per square inch         Operating Tempurature Range In Deg Celsius:         -53.89 to 51.67         Min. Tensile Strength (psi):         1200 pounds per square inch         Accessory Type:         Inner tube         Special Features:         Dual size army: used on 4k forklift         Special Features:         Dual size army: used on 4k forklift         Special Features:         Na         Departure From Cited Document:         As modified by size         Shelf Life:         N/a         Unit Of Measure:	Inflation Device Position:	
Regular   Base Construction:   Standard   Splice Minimum Rated Tensile Strength:   500 pounds per square inch   Operating Tempurature Range In Deg Celsius:   -53.89 to 51.67   Min. Tensile Strength (psi):   1200 pounds per square inch   Accessory Type:   Inner tube   Special Features:   Dual size army: used on 4k forklift   Specification Or Standard:   5 type   Departure From Cited Document:   As modified by size   Shelf Life:   N/a   Unit Of Measure:       Demilitarization:   No   Fig:	On center	
Base Construction: Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Construction:	
Standard Splice Minimum Rated Tensile Strength: 500 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Regular	
Splice Minimum Rated Tensile Strength: 500 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Base Construction:	
500 pounds per square inch Operating Tempurature Range In Deg Celsius: -53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Standard	
Operating Tempurature Range In Deg Celsius:         -53.89 to 51.67         Min. Tensile Strength (psi):         1200 pounds per square inch         Accessory Type:         Inner tube         Special Features:         Dual size army: used on 4k forklift         Specification Or Standard:         5 type         Departure From Cited Document:         As modified by size         Shelf Life:         N/a         Unit Of Measure:               Demilitarization:         No         Fig:	Splice Minimum Rated Tensile Strength:	
-53.89 to 51.67 Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	500 pounds per square inch	
Min. Tensile Strength (psi): 1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Operating Tempurature Range In Deg Celsius:	
1200 pounds per square inch Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	-53.89 to 51.67	
Accessory Type: Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Min. Tensile Strength (psi):	
Inner tube Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1200 pounds per square inch	
Special Features: Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Accessory Type:	
Dual size army: used on 4k forklift Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inner tube	
Specification Or Standard: 5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Special Features:	
5 type Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Dual size army: used on 4k forklift	
Departure From Cited Document: As modified by size Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Specification Or Standard:	
As modified by size Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	5 type	
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Departure From Cited Document:	
N/a Unit Of Measure:  Demilitarization: No Fiig:		
Unit Of Measure:  Demilitarization: No Fiig:		
 Demilitarization: No Fiig:		
No Fiig:	Unit Of Measure:	
No Fiig:	-	
Fiig:		
A009a0		