

View Online at <https://aerobasegroup.com/nsn/2610-01-126-1576>

**Tread Pattern:**

Traction

**Maximum Inflation Pressure:**

50.0 pounds per square inch

**End Application:**

M977, truck, cargo, tac, w/ow; m977, tac, 1 ot, 8x8; m978, truck, tanker, fuel, 8x8; m978, truck, tanker, tac, w/ow; m983, tractor, prime mover, 10 ton; m984, truck, wrecker, tac, 10 ton; m984a1, truck, wrecker, tac, 10 ton; m985 truck, cargo; m985e1

**Features Provided:**

Flaps

**Tire Air Retention Method:**

Tube type

**Tire Ply Arrangement:**

Radial

**Tire Load Maximum Capacity:**

8770.0 pounds load limits

**Tire Strength:**

M load range

**Tire And Size Designation:**

16.00r20 numeric

**Service Type:**

Off the road truck-bus

**Item Type Category:**

Tire

**Special Features:**

Goodyear at-2a load range "m". Sources must be pre-qualified per sae 2014, shipping size; od = 52.1

**Material:**

Rubber natural

**Specification Data:**

Sae j 2014 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A504s0