

View Online at <https://aerobasegroup.com/nsn/2610-01-148-1635>

Tread Pattern:

All season/mud-snow/lug

Maximum Inflation Pressure:

80.0 pounds per square inch

End Application:

Light truck trailer cargo m1008 truck cargo tac 1/4 4x4w m1008a1 truck cargo tac 1 1/4, 4 m1010 truck ambl 1 1/4t 4x4 m101a2 trailer cargo 3/4 ton m1028 truck cargo shelt.Co m1028a1 truck utility carr 4x4 m1028a3 truck utilitycarr 4x4 m1031 truck cargo comm cha m116a2 trailer cargo 3/4 ton rs28 roller vibratory sp-848 roller vibratory sp

Features Provided:

No flaps

Tire Air Retention Method:

Tubeless type

Tire Ply Arrangement:

Radial

Tire Load Maximum Capacity:

2778.0 pounds load limits

Tire Strength:

E load range

Tire And Size Designation:

Lt235/85r16 p-metric

Item Type Category:

Tire

Special Features:

Srevice type light truck cargo specification catl 1922 flap no amc-amsc 1-c tread all terrain lug mud snow load capacity (lbs) 2778 additional information group 2 weapon system: load /ply rating e construction radial category light truck trailer cargo m10008 truck cargo, tac, 1/4, 4x4w, m1008a1 truck, cargo, tac, 1 1/4, 4, m1010 truck, ambl, 1 1/4t, 4x4, m101a2 trailer, cargo, 3/4 ton, m1028 truck, cargo, shelt.Co, m1028a1 truck, utility carr, 4x4, m1028a3 truck, utility carr, 4x4, m1031 truck, cargo, comm cha, m116a2 trailer, cargo, 3/4 ton, rs28 roller, vibratory, sp-848 roller, vibratory, sp

Material:

Rubber natural

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A504s0