

View Online at <https://aerobasegroup.com/nsn/2610-01-171-4746>

**Tread Pattern:**

Traction

**Maximum Inflation Pressure:**

60.0 pounds per square inch

**End Application:**

M1025 truck, utility, arm, 4x4.W/e; m1026 truck, utility, arm, 4x4

**Features Provided:**

No flaps

**Tire Air Retention Method:**

Tubeless type

**Tire Ply Arrangement:**

Bias

**Tire Load Maximum Capacity:**

3350.0 pounds load limits

**Tire Strength:**

C load range

**Tire And Size Designation:**

36.00/12.50-16.50 numeric

**Service Type:**

Off the road light truck

**Special Features:**

Tire specification is restricted to manufacture, goodyear wrangler rt ii. Additional manufacturers must be pre approved per sae j 2014. Use caulking gun 2640-01-419-6200 use run flat device 2640-01-371-8332; you can order the a2 wheel kit (new configuration)

2530-01-443-3405 includes self locking nut, valve, inser, o-ring, rim assembly, valve cap and core

**Material:**

Rubber natural

**Specification Data:**

Sae j 2014 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A504s0