NSN 2610-01-333-7632

Vehicular Pneumatic Tire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2610-01-333-7632

trailer, cargo, 1.25 ton, m1113 truck, utility, 4x4, w/e, m116a3 trailer, chass

Traction
Maximum Inflation Pressure:
50.0 pounds per square inch
End Application:
M101a3 trailer, cargo, 1 ton, m1025 truck, utility, arm, 4x4
m1026 truck, utility, arm, 4x4, w/e, m1026a1 truck, utility,
soft top, m1035a2 truck, ambl, 4x4, 2 lit w/e, m1037 truck,

M101a3 trailer, cargo, 1 ton, m1025 truck, utility, arm, 4x4, w/e, m1025a1 truckutility, armt c, armd, 1.25 ton, m1025a2 truck, utility, 1.25 ton, m1026 truck, utility, arm, 4x4, w/e, m1026a1 truck, utility, armt c, armd, 1.25 ton, m1035 truck, ambl, 4x4, w/e, m1035a1 truck, ambl, 2lit, soft top, m1035a2 truck, ambl, 4x4, 2 lit w/e, m1037 truck, utility, w/e, 4x4, m1038 truck, utility, 1.25 ton, m1038a1 truck, utility, cargo/trp c, 1.25 ton, m1042 truck, utility, 1.25 ton, m1043 truck, utility, arm w/sa, m1043a1 truck, utility, armt c, w/sa, 1.25 ton, m1043a2 truck, utility, arm 4x4, w/e, m1044 truck, utility, 1.25 ton, m1044a1 truck, utility, armt c, w/sa 1.25 ton, m1045, truck, utility, tow, w/sa, m1045a1 truck, utility, tow c, w/sa, 1.25 ton, m1045a2 truck, utility, tow, w/sa, m1046 truck, utility, tow, sa ww, m1046a1 truck, utility, tow c, w/sa, 1.25 ton, m1097 truck, utility, hv, 10k, m1097a2 truck, utility, gvw, 4x4, w/e, m1101 trailer, cargo 3/4 ton, m1102

Features Provided:

Tread Pattern:

No flaps

Tire Air Retention Method:

Tubeless type

Tire Ply Arrangement:

Radial

Tire Load Maximum Capacity:

3850.0 pounds load limits

Tire Strength:

D load range

Tire And Size Designation:

Lt37x12.50r16.5lt p-metric

Service Type:

Off the road light truck

Special Features:

Use caulking gun 2640-01-419-6200; use run flat nsn 2640-01-419-6202; you can also order the a2 wheel kit (new configuration) nsn 2530-01-443-3405 which includes self locking nut, valve, insert, o-ring, rim assembly, valve cap and valve core. Warning: do not mix tires with different nsns on the same vehicle. Do not mix goodyear wrangler mt with goodyear wrangler mt/r tire on the same vehicle. Do not mix goodyear wranglermtwithmichelin bf goodrich baja tire on the same vehicle. Mixing tires with different nsns on the same vehicle can result in loss of vehicle control, serious injury or death to soldiers and damage to equipment.

М	ate	ria	I	:

Rubber natural

Specification Or Standard:

81343-sae-j-2014 design

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

. -- .