

View Online at <https://aerobasegroup.com/nsn/2610-01-373-7294>

Maximum Inflation Pressure:

120.0 pounds per square inch

End Application:

5 ton truck (m809, m813, m818) m900 series fuel tanker trailer (m920/m920a1/m969a2; m967/m967a1, m969/m969a1, m970/m970a1; m809 chassis truck, 5 ton; m969a2 trailer, tanker, fuel 5kg

Features Provided:

Flaps

Service Type And Tread Design:

Off the road truck-bus cross country

Tire Air Retention Method:

Tube type

Tire Ply Arrangement:

Radial

Tire Load Maximum Capacity:

7200.0 pounds load limits

Tire Strength:

H load range

Tire And Size Designation:

11.00r20 numeric

Service Type:

Off the road truck-bus

Special Features:

Includes flap p/n 11662389-2; tire specification is restricted to approved manufactures. Additional manufactures must be approved per sae j 2014. Tube 11.00r20 with tr444 valve p/n 12009348 cage 19200 can be used.

Material:

Rubber natural

Specification Data:

81348-sae-j-2014 professional/industrial association standard

Specification Or Standard:

X/g+3/tyrb/cla/t/11.00r20/h type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A504s0