

View Online at <https://aerobasegroup.com/nsn/2610-01-373-7294>

**Maximum Inflation Pressure:**

120.0 pounds per square inch

**End Application:**

5 ton truck (m809, m813, m818) m900 series fuel tanker trailer (m920/m920a1/m969a2; m967/m967a1, m969/m969a1, m970/m970a1; m809 chassis truck, 5 ton; m969a2 trailer, tanker, fuel 5kg

**Features Provided:**

Flaps

**Service Type And Tread Design:**

Off the road truck-bus cross country

**Tire Air Retention Method:**

Tube type

**Tire Ply Arrangement:**

Radial

**Tire Load Maximum Capacity:**

7200.0 pounds load limits

**Tire Strength:**

H load range

**Tire And Size Designation:**

11.00r20 numeric

**Service Type:**

Off the road truck-bus

**Special Features:**

Includes flap p/n 11662389-2; tire specification is restricted to approved manufactures. Additional manufactures must be approved per sae j 2014. Tube 11.00r20 with tr444 valve p/n 12009348 cage 19200 can be used.

**Material:**

Rubber natural

**Specification Data:**

81348-sae-j-2014 professional/industrial association standard

**Specification Or Standard:**

X/g+3/tyrb/cla/t/11.00r20/h type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A504s0