

View Online at <https://aerobasegroup.com/nsn/2610-01-500-4505>

Tread Pattern:

Grip regular

Maximum Inflation Pressure:

120.0 pounds per square inch

End Application:

Trailer, missile, patriot, m860a1, 2330-01-117-3280, 2330-01-054-9771; m681, trailer van, radar, 15 ton; m684, trailer van, exchg heat; m860a1 patriot missile launcher; m861 trailer van radar, 15 ton; m986 trailer launcher; m999, trailer, center control

Features Provided:

No flaps

Tire Air Retention Method:

Tubeless type

Tire Ply Arrangement:

Radial

Tire Load Maximum Capacity:

12300.0 pounds load limits

Tire Strength:

L load range

Tire And Size Designation:

445/65r22.5 numeric

Service Type:

Off the road truck-bus

Special Features:

Warning-bias tires 18.00-22.5 nsn 2610-01-115-2564 can not be mixed with radial tires 445/65r22.5 nsn 2610-01-500-4505 on same vehicle. When replacing a bias tire with radial, all tires must be replaced with radial nsn 2610-01-500-4505 on vehicle

Material:

Rubber natural

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A504s0