

View Online at <https://aerobasegroup.com/nsn/2610-01-500-4505>

**Tread Pattern:**

Grip regular

**Maximum Inflation Pressure:**

120.0 pounds per square inch

**End Application:**

Trailer, missile, patriot, m860a1, 2330-01-117-3280, 2330-01-054-9771; m681, trailer van, radar, 15 ton; m684, trailer van, exchg heat; m860a1 patriot missile launcher; m861 trailer van radar, 15 ton; m986 trailer launcher; m999, trailer, center control

**Features Provided:**

No flaps

**Tire Air Retention Method:**

Tubeless type

**Tire Ply Arrangement:**

Radial

**Tire Load Maximum Capacity:**

12300.0 pounds load limits

**Tire Strength:**

L load range

**Tire And Size Designation:**

445/65r22.5 numeric

**Service Type:**

Off the road truck-bus

**Special Features:**

Warning-bias tires 18.00-22.5 nsn 2610-01-115-2564 can not be mixed with radial tires 445/65r22.5 nsn 2610-01-500-4505 on same vehicle. When replacing a bias tire with radial, all tires must be replaced with radial nsn 2610-01-500-4505 on vehicle

**Material:**

Rubber natural

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A504s0