## NSN 2610-01-527-8260

**Tread Pattern:** 

Vehicular Pneumatic Tire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2610-01-527-8260

| Sand and desert tread  |
|--|
| Maximum Inflation Pressure:  |
| 70.0 pounds per square inch  |
| End Application:   |
| Marine corps lav under following nsn's 2320-01-494-7606, 2320-01-494-7611, 2320-01-49-47614, 2320-01-494-7616, 2320-01-494-7618, |
| 2320-01-494-7621, 5865-01-236-4235, wheel assembly nsn 2530015325635.  |
| Features Provided:   |
| No flaps   |
| Tire Air Retention Method:   |
| Tubeless type  |
| Tire Ply Arrangement:  |
| Radial   |
| Tire Load Maximum Capacity:  |
| 5070.0 pounds load limits  |
| Tire Strength:   |
| D load range   |
| Tire And Size Designation:   |
| 325/85r16 numeric  |
| Service Type:  |
| All terrain vehicle  |
| Special Features:  |
| Weapon system category logistics, c2, recovery, mewss usmc lav   |
| Material:  |
| Rubber synthetic   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A504s0   |
|  |
|  |