

View Online at <https://aerobasegroup.com/nsn/2610-01-572-6017>

**Tread Pattern:**

Cross country

**Maximum Inflation Pressure:**

120.0 pounds per square inch

**End Application:**

Mrap - unique nsn - mrap no permanent wsdc identified; nha: wheel assembly nsn 2530015706352, 2530015765896 weapon system category img maxxprodash matv mrap

**Features Provided:**

No flaps

**Tire Air Retention Method:**

Tubeless type

**Tire Ply Arrangement:**

Radial

**Tire Load Maximum Capacity:**

12300.0 pounds dynamic load

**Tire Strength:**

J load range

**Tire And Size Designation:**

395/85r20xzl numeric

**Service Type:**

Military truck-bus

**Special Features:**

Diameter 46.3 in; static load radius 21.1 in; free section width 15.4 in; loaded section width 16.8 in; revolutions/mile 451; thread width 13.1 in; thread droop .8 in; acr radius 22. In; thread depth 26 32nds; under thread thickness 7 32nds; regroovable depth 4 32nds; tire wieght 214.8 lbs; spring rate 7292.1 lbs/in; bead thickness 1.3 in; maximum speed 55 mph; ground contact area length 12.1 in, width 12.8 in, total area 136.1 in squared, net area 74.7 in squared

**Specification Data:**

Sae-j-2014 professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A504s0