NSN 2620-01-033-4860

Aircraft Pneumatic Tire - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/2620-01-033-4860

| Tread Pattern: | | | |
|--|--------------------|--|--|
| Rib multiple Maximum Inflation Pres | | | |
| | | | |
| 105.0 pounds per square Tire Air Retention Meth | | | |
| | <i>.</i> | | |
| Tubeless type Tire Ply Arrangement: | | | |
| Bias | | | |
| | | | |
| Tire Load Maximum Ca 3050.0 pounds static loa | | | |
| Tire Strength: | | | |
| 8 ply rating | | | |
| Tire And Size Designat | on: | | |
| 18x5.5 numeric | | | |
| Service Type: | | | |
| Aircraft main wheel | | | |
| Special Features: | | | |
| Ozone resistant | | | |
| Material: | | | |
| Plastic polyamide | | | |
| Specification Data: | | | |
| 81349-mil-t-5041 govern | nent specification | | |
| Specification Or Standa | | | |
| 7 type and 18x5.5 size | | | |
| Shelf Life: | | | |
| N/a | | | |
| Unit Of Measure: | | | |
| | | | |
| Demilitarization: | | | |
| No | | | |
| Fiig: | | | |
| A504s0 | | | |