

View Online at <https://aerobasegroup.com/nsn/2805-00-035-6819>

Casehardening Indicator:

Casehardened

Overall Height:

Between 0.4102 inches and 0.4182 inches

Thread Provision:

Unthreaded

Largest Inside Diameter:

Between 0.450 inches and 0.455 inches

Smallest Outside Diameter:

0.531 inches

Largest Outside Diameter:

Between 0.689 inches and 0.691 inches

Minimum Inside Diameter:

0.3415 inches

Smallest Outside Diameter Chamfer Angle In Deg:

30.0

First Ridge Radius:

Between 0.046 inches and 0.048 inches

Second Ridge Radius:

Between 0.046 inches and 0.048 inches

Third Ridge Radius:

Between 0.046 inches and 0.048 inches

Distance Between First And Second Ridge Centers:

Between 0.1596 inches and 0.1616 inches

Distance Between Second And Third Ridge Centers:

Between 0.1596 inches and 0.1616 inches

Distance From Bottom To First Ridge Center:

Between 0.045 inches and 0.047 inches

First Ridge Width:

Between 0.092 inches and 0.096 inches

Second Ridge Width:

Between 0.092 inches and 0.096 inches

Third Ridge Width:

Between 0.092 inches and 0.096 inches

Outside Included Angle In Deg:

23.4

Material:

Steel

Material:

Steel

Style Designator:

Straight bore-three ridges-bottom outer chamfer

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T267-h