

View Online at <https://aerobasegroup.com/nsn/2805-00-267-4673>

Cylinder Quantity:

12

Standard Bore Diameter:

5.7500 inches

Cooling Medium:

Liquid

Fording Feature:

Not included

Accessory Components And Quantity:

V3 air cleaner; 1 base mounting; 3 carburetor; 2 cooler, lubricating oil; 4 filter, lubricating oil; 1 generator, battery charging; 1 governor; 8 pumps, 6 electric, 2 mechanical; 2 pump, lubricating oil; 2 pump, sea water; 2 distributors

Reverse Speed Quantity:

1

Cylinder Arrangement:

Single v-type

Stroke Length:

7.0000 inches

Strokes Per Cycle:

4

Brake Horsepower At Specificationified Rpm:

450.0000 bhp at 1800.000 rpm

Direct Raw Water Cooling Feature:

Included

Closed System Hull Cooling Feature:

Not included

Cylinder Head Type:

I-head

Fuel Induction Type:

Carburetor

Ignition Type:

Battery

Dual Ignition System:

Included

Crankshaft Rotation Direction:

Clockwise

Starting Method:

Electrical

Supercharger:

Not included

Flywheel:

Included

Flywheel Housing:

Included

Reduction Gear:

Not included

Fluid Coupling:

Not included

Transmission:

Included

Transmission Type:

Manual

Forward Speed Quantity:

1

Overdrive:

Not included

Cross Drive:

Not included

Clutch:

Included

Main Power Takeoff Rotation Direction:

Clockwise

Engineheight:

47.200 inches

Enginewidth:

88.000 inches

Enginewidth:

45.400 inches

Starter:

Included

Electromagnetic Interference Suppression:

Not provided

Voltage In Volts:

24.0

Special Features:

Deep oil sump, sea water cooled, bilge pump atchd

Weight:

3600.000 pounds

Reference Number Differentiating Characteristics:

Cooling medium, starting method, accessory components and quantity, and special features requirements

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T197-a