NSN 2805-00-274-3408

Engine Poppet Valve - Page 1 of 2

Head Style:Concave



View Online at https://aerobasegroup.com/nsn/2805-00-274-3408

Head Height:
Between 0.2620 inches and 0.2820 inches
Chamfer Angle In Deg:
45.0
Chamfer Length:
0.0312 inches
Taper Angle In Deg:
20.0
Outside Diameter:
Between 0.7470 inches and 2.7530 inches
Minor Outside Diameter:
0.3906 inches
Minor Diameter Length:
Any acceptable
Seat Angle In Deg:
30.0
Stem Style:
Tapered multi-grooved
Carbon Relief Groove:
Not included
Neck Radius:
0.8750 inches
Stem Length:
Between 5.8340 inches and 5.8390 inches
Stem Diameter:
Between 0.5270 inches and 0.5280 inches
Distance From First Groove To Stem End:
0.1490 inches
Distance From Second Groove To Stem End:
0.3090 inches
Distance From Third Groove To Stem End:
0.4690 inches
First Groove Diameter:
Between 0.3390 inches and 0.3440 inches
Second Groove Diameter:
Between 0.3390 inches and 0.3440 inches
Third Groove Diameter:
Between 0.3390 inches and 0.3440 inches
First Groove Width:

Between 0.1000 inches and 0.1020 inches

NSN 2805-00-274-3408

Engine Poppet Valve - Page 2 of 2



Second	Groove	Width:

Between 0.1000 inches and 0.1020 inches

Third Groove Width:

Between 0.1000 inches and 0.1020 inches

Material And Location:

Steel stem

Metallic Hardness Rating And Location:

80.0 rockwell c tip

Fsc Application Data:

Gasoline engine

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A11200