NSN 2805-00-293-9665

Engine Poppet Valve - Page 1 of 2

Head Style:



View Online at https://aerobasegroup.com/nsn/2805-00-293-9665

neau Style.
Flat
Head Height:
0.1719 inches
Chamfer Angle In Deg:
45.0
Chamfer Length:
0.0312 inches
Outside Diameter:
Between 1.5250 inches and 1.5350 inches
Seat Angle In Deg:
45.0
Stem Style:
Double grooved
Carbon Relief Groove:
Not included
Neck Radius:
0.3125 inches
Stem Length:
Between 5.7413 inches and 5.7623 inches
Stem Diameter:
Between 0.3722 inches and 0.3730 inches
Distance From First One and To Otem Fords
Distance From First Groove To Stem End:
0.1875 inches
0.1875 inches
0.1875 inches Distance From Second Groove To Stem End:
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter:
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter:
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width:
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width:
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1250 inches
O.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1250 inches Material And Location:
0.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1250 inches Material And Location: Steel, federal standard 66, sae hnv3
O.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1250 inches Material And Location: Steel, federal standard 66, sae hnv3 Metallic Hardness Rating And Location:
O.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1250 inches Material And Location: Steel, federal standard 66, sae hnv3 Metallic Hardness Rating And Location: 50.0 rockwell c tip
O.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1250 inches Material And Location: Steel, federal standard 66, sae hnv3 Metallic Hardness Rating And Location: 50.0 rockwell c tip Fsc Application Data:
O.1875 inches Distance From Second Groove To Stem End: 0.6406 inches First Groove Diameter: Between 0.2980 inches and 0.3040 inches Second Groove Diameter: Between 0.3310 inches and 0.3380 inches First Groove Width: Between 0.0950 inches and 0.1050 inches Second Groove Width: 0.1250 inches Material And Location: Steel, federal standard 66, sae hnv3 Metallic Hardness Rating And Location: 50.0 rockwell c tip Fsc Application Data: Gasoline engine

NSN 2805-00-293-9665

Engine Poppet Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A11200