NSN 2805-00-361-2538

Engine Poppet Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2805-00-361-2538 **Head Style:**

| Flat |
|---|
| Head Height: |
| 0.1875 inches |
| Chamfer Angle In Deg: |
| 45.0 |
| Chamfer Length: |
| 0.0312 inches |
| Outside Diameter: |
| Between 1.7440 inches and 1.7540 inches |
| Seat Angle In Deg: |
| 44.0 |
| Stem Style: |
| Double grooved |
| Carbon Relief Groove: |
| Not included |
| Neck Radius: |
| 0.3125 inches |
| Stem Length: |
| 4.9375 inches |
| Stem Diameter: |
| Between 0.3710 inches and 0.3720 inches |
| Distance From First Groove To Stem End: |
| 0.3437 inches |
| Distance From Second Groove To Stem End: |
| 0.5000 inches |
| First Groove Diameter: |
| Between 0.3020 inches and 0.3080 inches |
| Second Groove Diameter: |
| Between 0.3020 inches and 0.3080 inches |
| First Groove Width: |
| 0.0625 inches |
| Second Groove Width: |
| 0.0625 inches |
| Material And Location: |
| Bronze, steel backed, no. le419, caterpillar tractor co |
| Metallic Hardness Rating And Location: |
| 67.0 rockwell superficial 30-n tip err-100 |
| Fsc Application Data: |
| Gasoline engine |
| Shelf Life: |
| N/a |

NSN 2805-00-361-2538

Engine Poppet Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A11200