## NSN 2805-00-362-0551

**Cross Sectional Shape:** 

**Shaft Connecting End Style:** 2 bolt mounted solid sleeve

**Fabrication Method:** 

I-section type

Any acceptable

Piston Connecting Rod - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2805-00-362-0551

End Thickness:
0.875 inches
Edge Radius:
1.125 inches
End Hole Inside Diameter:
0.875 inches
Piston Connecting End Bearing:
Included
Bearing Replaceability:
Replaceable
Piston Connecting End Lubrication Drill Feature:
Included
Piston Connecting End Lubrication Method:
Splash
Shaft Connecting End Bearing:
Included
Shaft Connecting End Hole Inside Diameter:
1.562 inches
Shaft Connecting End Edge Radius:
2.188 inches
Shaft Connecting End Width:
4.500 inches
Shaft Connecting End Thickness:
2.000 inches
Shaft Connecting End Bearing Replaceability:
Replaceable
Shaft Connecting End Lubrication Drill Feature:
Included
Shaft Connecting End Lubrication Method:
Splash
Center To Center Effective Length:
10.813 inches
Body Width At Piston Connecting End:
1.188 inches
Body Width At Shaft Connecting End:
1.375 inches

## NSN 2805-00-362-0551

Piston Connecting Rod - Page 2 of 2



<b>Body Thickness At Piston Connecting End:</b>
0.906 inches
Body Thickness At Shaft Connecting End:
0.906 inches
Piston End Connection Style:
Small engine and automotive standard
Material:
Steel
Material:
Steel
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No **Fiig:** T267-d