NSN 2805-00-419-9402

Casehardening Indicator:

Concentric Hole Depth:

Concentric Hole Diameter:

Not casehardened

Any acceptable

Any acceptable

Overall Length:

Engine Poppet Valve Tappet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2805-00-419-9402

| Between 1.830 inches and 1.860 inches | | | | | |
|--|--|--|--|--|--|
| Boss Diameter: | | | | | |
| Any acceptable | | | | | |
| Body Groove Width: | | | | | |
| 0.183 inches | | | | | |
| Spherical Radius: | | | | | |
| Any acceptable | | | | | |
| Size Designation: | | | | | |
| Standard | | | | | |
| Material And Location: | | | | | |
| Iron, cast body | | | | | |
| Adjustability: | | | | | |
| Nonadjustable | | | | | |
| Operation Method: | | | | | |
| Hydraulic | | | | | |
| Metallic Hardness Rating And Location: | | | | | |
| 55.0 rockwell c face | | | | | |
| Cam End Diameter: | | | | | |
| 0.904 inches | | | | | |
| Distance From Boss Face To Cam End: | | | | | |
| Any acceptable | | | | | |
| Body Hole Diameter: | | | | | |
| 0.094 inches | | | | | |
| Distance From Body Hole Center To Cam End: | | | | | |
| 1.313 inches | | | | | |
| Cup Spherical Radius: | | | | | |
| Between 0.547 inches and 0.551 inches | | | | | |
| Body Groove Diameter: | | | | | |
| 0.938 inches | | | | | |
| Distance From Body Groove Center To Cam End: | | | | | |
| 1.281 inches | | | | | |
| Style Designator: | | | | | |
| Chamfered, concentric hole push rod end | | | | | |
| Shelf Life: | | | | | |
| N/a | | | | | |
| | | | | | |

NSN 2805-00-419-9402

Engine Poppet Valve Tappet - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

T267-f