NSN 2805-00-517-9932

Engine Poppet Valve - Page 1 of 2

Head Style:



View Online at https://aerobasegroup.com/nsn/2805-00-517-9932

Mushroom		
Head Height:		
0.1570 inches		
Chamfer Angle In Deg:		
30.0		
Groove Diameter:		
Between 0.4550 inches and 0.4600 inches		
Chamfer Length:		
0.1360 inches		
Groove Width:		
0.2500 inches		
Taper Angle In Deg:		
15.0		
Outside Diameter:		
Between 1.8800 inches and 1.8900 inches		
Minor Outside Diameter:		
Between 0.3950 inches and 0.3990 inches		
Minor Diameter Length:		
Between 0.0350 inches and 0.0400 inches		
Seat Angle In Deg:		
44.0		
Stem Style:		
Stem Style: Tapered and grooved		
•		
Tapered and grooved		
Tapered and grooved Carbon Relief Groove:		
Tapered and grooved Carbon Relief Groove: Not included		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius:		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length:		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches Stem Diameter:		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches Stem Diameter: Between 0.4940 inches and 0.4950 inches		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches Stem Diameter: Between 0.4940 inches and 0.4950 inches Distance From Minor Diameter To Stem End:		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches Stem Diameter: Between 0.4940 inches and 0.4950 inches Distance From Minor Diameter To Stem End: Between 0.4050 inches and 0.4070 inches		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches Stem Diameter: Between 0.4940 inches and 0.4950 inches Distance From Minor Diameter To Stem End: Between 0.4050 inches and 0.4070 inches Distance From Groove To Stem End:		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches Stem Diameter: Between 0.4940 inches and 0.4950 inches Distance From Minor Diameter To Stem End: Between 0.4050 inches and 0.4070 inches Distance From Groove To Stem End: Between 0.8700 inches and 0.8800 inches		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches Stem Diameter: Between 0.4940 inches and 0.4950 inches Distance From Minor Diameter To Stem End: Between 0.4050 inches and 0.4070 inches Distance From Groove To Stem End: Between 0.8700 inches and 0.8800 inches Material And Location:		
Tapered and grooved Carbon Relief Groove: Not included Neck Radius: 0.3750 inches Stem Length: 6.4060 inches Stem Diameter: Between 0.4940 inches and 0.4950 inches Distance From Minor Diameter To Stem End: Between 0.4050 inches and 0.4070 inches Distance From Groove To Stem End: Between 0.8700 inches and 0.8800 inches Material And Location: Steel stem		

Gasoline engine

NSN 2805-00-517-9932

Engine Poppet Valve - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A11200