

View Online at <https://aerobasegroup.com/nsn/2805-00-575-4816>

Cylinder Quantity:

6

Standard Bore Diameter:

3.438 inches

Cooling Medium:

Liquid

Fording Feature:

Not included

Accessory Components And Quantity:

Air cleaner 1, carburetor 1, generator, battery charging 1, filter, lubricating oil 1, pump, fuel 1, regulator, voltage 1, spark plugs 6

Cylinder Arrangement:

Straight in-line

Stroke Length:

4.375 inches

Strokes Per Cycle:

4

Brake Horsepower At Specificationified Rpm:

102 bhp at 3200 rpm

Direct Raw Water Cooling Feature:

Not included

Closed System Hull Cooling Feature:

Included

Cylinder Head Type:

L-head

Fuel Induction Type:

Carburetor

Ignition Type:

Battery

Dual Ignition System:

Not included

Crankshaft Rotation Direction:

Counterclockwise

Starting Method:

Electrical

Supercharger:

Not included

Flywheel:

Included

Flywheel Housing:

Included

Reduction Gear:

Not included

Fluid Coupling:

Not included

Transmission:

Not included

Clutch:

Not included

Main Power Takeoff Rotation Direction:

Clockwise

Starter:

Included

Electromagnetic Interference Suppression:

Provided

Voltage In Volts:

12.0

Fsc Application Data:

19405260207, boat, bridge erection, combined metal mfg corporation model 27ft, 19402726400, boat, bridge erection, correct craft inc model 19ft, 19403554469, boat, bridge erection, higgins inc model t-1-50, 19408094472, boat, bridge erection, highway products co model hp127b, 19405677898, boat, bridge erection, lone star boat mfg co model lone star, 19407106649, boat, bridge erection, marinette marine corporation model a27

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T197-a