

View Online at <https://aerobasegroup.com/nsn/2805-00-625-8219>

Casehardening Indicator:

Casehardened

Concentric Hole Depth:

Between 1.705 inches and 1.725 inches

Concentric Hole Diameter:

Between 1.690 inches and 1.710 inches

Overall Length:

Between 1.895 inches and 1.905 inches

Boss Diameter:

Between 0.490 inches and 0.510 inches

Body Groove Width:

Between 0.590 inches and 0.610 inches

Spherical Radius:

30.000 inches

Size Designation:

Standard

Casehardened Location:

Material And Location:

Steel, cast

Adjustability:

Nonadjustable

Operation Method:

Mechanical

Metallic Hardness Rating And Location:

55.0 rockwell c and 60.0 rockwell c

Cam End Diameter:

Between 1.9170 inches and 1.9172 inches

Distance From Boss Face To Cam End:

Between 0.2040 inches and 0.2059 inches

Body Hole Diameter:

Between 0.240 inches and 0.260 inches

Distance From Body Hole Center To Cam End:

Between 1.250 inches and 1.270 inches

Body Groove Diameter:

Between 1.895 inches and 1.905 inches

Distance From Body Groove Center To Cam End:

Between 0.890 inches and 0.910 inches

Style Designator:

Chamfered, concentric hole push rod end

Fsc Application Data:

Engine, gasoline, nonaircraft

Reference Number Differentiating Characteristics:

As differentiated by distance from boss face to cam end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T267-f