NSN 2805-00-626-0359

Engine Poppet Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/2805-00-626-0359

Head Style:
Mushroom
Head Height:
Between 0.2490 inches and 0.2910 inches
Chamfer Angle In Deg:
30.0
Chamfer Length:
0.0312 inches
Outside Diameter:
Between 1.5340 inches and 1.5440 inches
Seat Angle In Deg:
44.0
Carbon Relief Groove:
Not included
Neck Radius:
0.4375 inches
Stem Length:
5.6990 inches
Stem Diameter:
Between 0.4335 inches and 0.4345 inches
Distance From First Groove To Stem End:
0.3900 inches
0.3900 inches Distance From Second Groove To Stem End:
Distance From Second Groove To Stem End:
Distance From Second Groove To Stem End: 0.5460 inches
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter:
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter:
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter:
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width:
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width: Between 0.0302 inches and 0.0322 inches
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width: Between 0.0302 inches and 0.0322 inches Second Groove Width:
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width: Between 0.0302 inches and 0.0322 inches Second Groove Width: 0.0302 mils and 0.0322 centimeters
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width: Between 0.0302 inches and 0.0322 inches Second Groove Width: 0.0302 mils and 0.0322 centimeters Third Groove Width:
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width: Between 0.0302 inches and 0.0322 inches Second Groove Width: 0.0302 mils and 0.0322 centimeters Third Groove Width: 4.0000 inches
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width: Between 0.0302 inches and 0.0322 inches Second Groove Width: 0.0302 mils and 0.0322 centimeters Third Groove Width: 4.0000 inches Metallic Hardness Rating And Location:
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width: Between 0.0302 inches and 0.0322 inches Second Groove Width: 0.0302 mils and 0.0322 centimeters Third Groove Width: 4.0000 inches Metallic Hardness Rating And Location: 47.0 rockwell c stem err-100
Distance From Second Groove To Stem End: 0.5460 inches First Groove Diameter: Between 0.3630 inches and 0.3690 inches Second Groove Diameter: Between 0.3630 inches and 0.3690 inches Third Groove Diameter: Between 0.3840 inches and 0.3940 inches First Groove Width: Between 0.0302 inches and 0.0322 inches Second Groove Width: 0.0302 mils and 0.0322 centimeters Third Groove Width: 4.0000 inches Metallic Hardness Rating And Location: 47.0 rockwell c stem err-100 Fsc Application Data:

NSN 2805-00-626-0359

Engine Poppet Valve - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A11200