
## NSN 2805-00-629-6853

Piston Connecting Rod - Page 1 of 2





**Cross Sectional Shape:** I-section type **Fabrication Method:** Cast and machined Shaft Connecting End Style: Automotive standard split bearing 2 bolt End Thickness: 0.730 inches **Edge Radius:** 0.473 inches End Hole Inside Diameter: 0.418 inches **Piston Connecting End Bearing:** Not included **Piston Connecting End Lubrication Drill Feature:** Not included **Piston Connecting End Lubrication Method:** Splash Shaft Connecting End Bearing: Not included Shaft Connecting End Hole Inside Diameter: 0.878 inches Shaft Connecting End Edge Radius: 0.824 inches Shaft Connecting End Width: 1.754 inches Shaft Connecting End Thickness: 0.714 inches Shaft Connecting End Lubrication Drill Feature: Included Shaft Connecting End Lubrication Method: Splash Center To Center Effective Length: 3.875 inches **Body Width At Piston Connecting End:** 0.540 inches Body Width At Shaft Connecting End: 0.625 inches **Body Thickness At Piston Connecting End:** 0.450 inches Body Thickness At Shaft Connecting End: 0.450 inches

## NSN 2805-00-629-6853

Piston Connecting Rod - Page 2 of 2



**Piston End Connection Style:** Small engine and automotive standard **Special Features:** Grumman aerospace a-10 aircraft Material: Aluminum alloy Material: Aluminum alloy Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: T267-d